



# Sniper Holdings

See The Light Special

# UNI-T®

EXCL. VAT  
**R725.00**

## UT136B+ PALM SIZE MULTIMETER



- AC/DC Voltage: 1000V
- AC/DC Current: 10A
- Frequency: 400Hz ~ 40MHz
- Capacitance: 40mF
- hFE: Transistor Test
- NCV: Non-Contact Voltage
- Safety: CAT II 1000V / CAT III 600V
- Display: 4000 Count Backlight
- Durability: 2m Drop Proved

EXCL. VAT  
**R499.00**

## UT133B PALM SIZE MULTIMETER



- AC/DC Voltage: 600V
- DC Current: 10A
- Resistance: 60MΩ
- Capacitance: 9.999mF ~ 99.99mF
- Battery Test: 1.5V/9V Status
- Safety: CAT II 600V
- Display: 6000 Count Backlight
- Durability: 2m Drop Proved

EXCL. VAT  
**R580.00**

## UT133A PALM SIZE MULTIMETER



- AC/DC Voltage: 600V
- AC/DC Current: 10A
- Resistance: 60MΩ
- Capacitance: 9.999mF ~ 99.99mF
- Frequency: 10Hz ~ 1MHz
- Temperature: -40°C ~ 1000°C
- Safety: CAT II 600V
- Display: 6000 Count Backlight

EXCL. VAT  
**R485.00**

## UT121B SMART DIGITAL MULTIMETER+



- AC/DC Voltage: 600V
- Frequency: 10Hz ~ 10MHz
- Capacitance: 60mF
- Resistance: 60MΩ
- NCV: Non-Contact Voltage
- Temperature: -40°C ~ 1000°C
- Display: 6000 Count EBTN
- Design: 19mm Ultra-thin Case

EXCL. VAT  
**R822.00**

## UT118C PEN TYPE DIGITAL MULTIMETER



- AC/DC Voltage: 600V
- Capacitance: 1nF ~ 100mF
- Resistance: 0.1Ω ~ 60MΩ
- Frequency: 10Hz ~ 10MHz
- NCV: Non-Contact Voltage
- Duty Cycle: 0.1% ~ 99.9%
- Safety: CAT III 600V
- Display: 6000 Count Backlight

EXCL. VAT  
**R5999.00**

## UT311A VIBRATION TESTER



- Acceleration: 0.1~199.9m/s2
- Velocity: 0.1~199.9mm/s
- Displacement: 0.001~1.999mm
- Frequency Range: 10Hz~10kHz
- Accuracy: ±5%+2 digits
- Measurement Modes: RMS / Peak
- Display: 2000 Count with Backlight
- Features: Data Hold / Auto Power Off
- Safety/Cert: CE / RoHS Compliant

EXCL. VAT  
**R775.00**

## UT136C+ PALM SIZE MULTIMETER



- AC/DC Voltage: 1000V
- AC/DC Current: 10A
- Resistance: 40MΩ
- Capacitance: 40mF
- Frequency: 400Hz ~ 40MHz
- Temperature: -40°C ~ 1000°C
- Safety: CAT II 1000V / CAT III 600V
- Display: 4000 Count Backlight
- Durability: 2m Drop Proved

EXCL. VAT  
**R5899.00**

## UT705 SINGLE FUNCTION CALIBRATOR



- DC Voltage: 0V ~ 30V
- DC Current: 0mA ~ 24mA
- Loop Power: 24V Active Output
- Measurement: Voltage/ Current/Loop
- Source: Current Output
- Step/Ramp: Auto/Manual Functions
- Precision: High Accuracy 0.02%
- Display: LCD with Backlight

EXCL. VAT  
**R4999.00**

## UT501E INSULATION RESISTANCE TESTER



- Output Voltage: 250V / 500V / 1000V
- Insulation Range: 0.01MΩ ~ 5GΩ
- AC/DC Voltage: 30V ~ 600V
- DAR/PI: Auto Calculation
- Data Storage: 99 Group Memory
- Safety: CAT III 600V
- Display: 2000 Count Backlight
- Low Battery: Automatic Indication



# Sniper Holdings

See The Light Special

# UNI-T®

EXCL VAT 00  
**R7199.00**

## UT205E 1000A AC DIGITAL CLAMP METER



- AC Current: 1000A
- AC/DC Voltage: 1000V
- Resistance: 60MΩ
- Capacitance: 60mF
- Frequency: 10Hz ~ 10MHz
- Duty Cycle: 0.1% ~ 99.9%
- Safety: CAT II 1000V / CAT III 600V
- Display: 6000 Count Backlight

EXCL VAT 00  
**R1299.00**

## UT216A 600A DIGITAL CLAMP METER



- AC Current: 600A
- AC/DC Voltage: 600V
- Resistance: 60MΩ
- Capacitance: 60mF
- Frequency: 10Hz ~ 1MHz
- NCV: Non-Contact Voltage
- True RMS: Accurate Measurement
- Flashlight: Built-in LED
- Safety: CAT II 600V / CAT III 600V
- Display: 6000 Count Backlight

EXCL VAT 00  
**R999.00**

## 2117R 1000A AC CLAMP METER



- AC Current: 1000A (True RMS)
- AC/DC Voltage: 1000V
- Resistance: 60MΩ
- Capacitance: 6mF
- ACA Frequency: 20Hz ~ 10kHz
- NCV: Dual-mode (High/Low)
- Safety: CAT II 1000V / CAT III 600V
- Display: 6000 Count Backlight
- Overload Protection: 1000V across all ranges

EXCL VAT 00  
**R4999.00**

## UT222 2500A AC/DC DIGITAL CLAMP METER



- AC/DC Current: 2500A
- AC/DC Voltage: 1000V
- Resistance: 60MΩ
- Capacitance: 60mF
- Frequency: 60MHz
- Temperature: -40°C ~ 1000°C
- Jaw Opening: 63mm Large Jaw
- Features: True RMS / Inrush Current / LPF
- Safety: CAT III 1000V / CAT IV 600V
- Display: 6000 Count with Bar Graph

EXCL VAT 00  
**R690.00**

## UT256 60A DIGITAL FORK METER



- AC Current: 60A
- AC/DC Voltage: 600V
- Resistance: 60MΩ
- Capacitance: 60mF
- Frequency: 10Hz ~ 1MHz
- True RMS: For accurate non-linear loads
- Design: Open jaw fork for easy access
- Safety: CAT III 600V
- Display: 6000 Count Backlight

EXCL VAT 00  
**R1399.00**

## UT210D 200A AC/DC MINI CLAMP METER



- AC/DC Current: 200A (True RMS)
- AC/DC Voltage: 600V
- Resistance: 20MΩ
- Capacitance: 20mF
- Frequency: 10Hz ~ 60kHz
- Temperature: -40°C ~ 1000°C
- NCV: Non-Contact Voltage
- Features: Zero Mode / Data Hold
- Safety: CAT II 600V / CAT III 300V
- Display: 2000 Count Backlight

EXCL VAT 00  
**R3499.00**

## UT362H HOT WIRE ANEMOMETER



- Wind Velocity: 0 ~ 30m/s
- Wind Volume: 0 ~ 999,900 m3/min (CFM / L/s)
- Temperature: -20°C ~ 70°C
- Sensor: Platinum Resistance (High Stability)
- Probe: 120cm Flexible/Retractable Rod
- Data Storage: 99 Sets
- Modes: Max/Min / Avg / Fast & Slow Sampling
- Display: Large LCD with Backlight
- Safety/Cert: CE / RoHS Compliant

EXCL VAT 00  
**R3299.00**

## UT303C+ INFRARED THERMOMETER



- Temperature Range: -32°C ~ 1100°C
- D:S Ratio: 30:1 (Distance to Spot)
- Emissivity: 0.1 ~ 1.0 Adjustable
- Accuracy: ±1.5% or ±1.5°C
- Response Time: 250ms
- Spectral Response: 8μm ~ 14μm
- Features: High/Low Temp Alarm
- Display: EBTN Color Display
- Power: 9V Battery or USB Power

EXCL VAT 00  
**R299.00**

## UT12M VOLTAGE DETECTOR



- Voltage Range: 24V ~ 1000V
- Frequency: 50Hz / 60Hz
- Magnetic Solenoid: Detection Mode
- Dual Mode: Low/High Sensitivity
- Alerts: Visual & Audible Alarm
- Safety: CAT IV 1000V
- Durability: IP67 Dust & Water Proof
- LED Flashlight: Built-in Torch



# Sniper Holdings

See The Light Special

# UNI-T®

EXCL VAT  
**R697.00**

## LM40MI MINI LASER DISTANCE METER

- Range: 0.05m ~ 40m
- Accuracy:  $\pm(2.0\text{mm}+5\times 10^{-5}\text{D})$
- Measurement Modes: Area / Volume / Perimeter / Pythagoras
- Battery: 3.7V 370mAh Lithium (Rechargeable via Type-C)
- Battery Life: 8000 measurements per full charge
- Display: LCD with Backlight
- Unit Options: m / ft / in
- Laser Class: Class II (630nm ~ 670nm, <1mW)
- Design: Ultra-compact (86.5 x 36.5 x 19.5mm)
- Construction: Durable metal shell



EXCL VAT  
**R556.00**

## LM50A LASER DISTANCE METER

- Range: 0.05m ~ 50m
- Accuracy:  $\pm(2.0\text{mm}+5\times 10^{-5}\text{D})$
- Measurement Modes: Area / Volume / Pythagoras
- Reference Points: Front / Rear
- Unit Options: m / ft / in / ft+in
- Laser Class: Class II (630nm ~ 670nm, <1mW)
- Display: 2.0-inch Large TN Screen
- Memory: 30 Sets of Data Storage
- Design: Ergonomic Anti-slip Grip
- Safety/Cert: CE / RoHS Compliant



EXCL VAT  
**R775.00**

## LM60MI MINI LASER DISTANCE METER

- Range: 0.05m ~ 60m
- Accuracy:  $\pm(2.0\text{mm}+5\times 10^{-5}\text{D})$
- Measurement Modes: Area / Volume / Perimeter / Pythagoras
- Battery: 3.7V 370mAh Lithium (Rechargeable via Type-C)
- Battery Life: 8000 measurements per full charge
- Display: LCD Backlight
- Unit Options: m / ft / in
- Laser Class: Class II (630nm ~ 670nm, <1mW)
- Design: Ultra-compact (86.5 x 36.5 x 19.5mm)
- Construction: Durable metal shell



EXCL VAT  
**R1100.00**

## LM570LD-II CROSS LINE LASER LEVEL

- Laser Type: Green Beam (High Visibility)
- Wavelength: 520nm
- Operating Distance: 20m ~ 40m
- Accuracy:  $\pm 3\text{mm}/10\text{m}$
- Self-Leveling Range:  $3\circ \pm 1\circ$
- Lines: 2-Line (Vertical and Horizontal)
- Power: 2 x AA Batteries
- Design: Compact and Easy to Use
- Mounting: 1/4 inch Tripod Thread
- Safety/Cert: CE / RoHS Compliant



EXCL VAT  
**R2199.00**

## LM600G LASER RANGEFINDER

- Range: 5m ~ 600m
- Accuracy:  $\pm 1\text{m}\pm(D\times 0.2\%)$
- Magnification: 6X
- Objective Lens: 24mm
- Measurement Modes: Distance / Angle / Height / Speed / Slope Compensation
- Speed Range: 0 ~ 300km/h
- Angle Range:  $\pm 45\circ$
- Battery: 1500mAh Li-ion (Rechargeable)



EXCL VAT  
**R1999.00**

## LM600 LASER RANGEFINDER

- Range: 5m ~ 600m
- Accuracy:  $\pm 1\text{m}\pm(D\times 0.2\%)$
- Magnification: 6X
- Objective Lens: 24mm
- Measurement Modes: Distance / Angle / Height / Speed
- Speed Range: 0 ~ 300km/h
- Angle Range:  $\pm 45\circ$
- Battery: 1500mAh Li-ion (Rechargeable)
- Display: Through-the-lens LCD
- Features: Pulse Laser (eye-safe) / Silent Operation / Lightweight Design



EXCL VAT  
**R860.00**

## UT-D07B BLUETOOTH ADAPTER

- Function: Converts serial data to wireless Bluetooth.
- Compatibility: Works with UNI-T UT71, UT171, and UT181 series.
- Connectivity: Bluetooth 5.0 (Low Energy).
- Distance: Up to 10 meters.
- App Support: Compatible with iDMM or Uni-T Hub.
- Features: Real-time logging and data export (CSV/PDF).
- Power: Draws power directly from the host device.



EXCL VAT  
**R160.00**

## UT-C02B ALLIGATOR CLIP

- Type: Large-mouth alligator clip.
- Safety: CAT III 1000V / CAT IV 600V.
- Rating: 10A current.
- Opening: 22mm aperture.
- Socket: 4mm standard connection.
- Design: Fully insulated for safety.



EXCL VAT  
**R288.00**

## A61 DIGITAL PROBE THERMOMETER

- Measurement Range:  $-50\text{C} \sim 200\text{C}$
- Accuracy:  $\pm 1\text{C}$  ( $-20\text{C} \sim 100\text{C}$ )
- Probe Length: 120mm (Stainless Steel)
- LED Indication: Color alerts for temperature thresholds
- Protection: IP65 Water and Dust resistant
- Display: LCD with Backlight
- Features: Data Hold / Max-Min / Auto Power Off
- Application: Suitable for liquids (water, oil), food, and ovens





# Sniper Holdings

## See The Light Special

# UNI-T®

EXCL. VAT 00  
R19390.00

### B20S HANDHELD THERMAL IMAGING CAMERA

- IR Resolution: 320×240 (76,800 pixels)
- SuperIR: 640×480 (307,200 pixels)
- NETD: < 40mK
- Image Frequency: 25Hz
- FOV: 50°×37.2°
- Visual Camera: 1600×1200 (2MP)
- Display: 3.2" LCD (240×320 resolution)
- Object Temp Range: -20°C ~ 550°C
- Accuracy: Max (±2°C)
- Storage: Built-in 16GB (Up to 90,000 images)
- Battery: Approx. 6 hours (USB Type-C)
- Durability: IP54, 2m Drop Protection

EXCL. VAT 00  
R9080.00

### B11 HANDHELD THERMAL IMAGING CAMERA

- IR Resolution: 192×144 (27,648 pixels)
- SuperIR: 320×240 (76,800 pixels)
- NETD: < 40mK
- Image Frequency: 25Hz
- FOV: 27.8°×37.2°
- Visual Camera: 1600×1200 (2MP)
- Display: 3.2" LCD (240×320 resolution)
- Object Temp Range: -20°C ~ 550°C
- Accuracy: Max (±2°C)
- Storage: Built-in 16GB (Up to 90,000 images)
- Battery: Approx. 6 hours (USB Type-C)
- Durability: IP54, 2m Drop Protection

EXCL. VAT 00  
R18880.00

### M11W HANDHELD THERMAL IMAGING CAMERA

- IR Resolution: 192×144 (27,648 pixels)
- SuperIR: 384×288 (110,592 pixels)
- NETD: < 40mK
- Image Frequency: 25Hz
- FOV: 37.2°×27.8°
- Visual Camera: 3264×2448 (8MP)
- Display: 3.2" LCD Touch Screen (640×480 resolution)
- Object Temp Range: -20°C ~ 550°C
- Accuracy: Max (±2°C)
- Storage: Removable 32GB SD Card (Up to 60,000 images)
- Connectivity: Wi-Fi (2.4GHz) & Bluetooth 4.2
- Battery: Approx. 6 hours (USB Type-C)
- Features: Laser Pointer, LED Flashlight, IP54, 2m Drop Protection

EXCL. VAT 00  
R8999.00



### POCKET-E HANDHELD THERMAL IMAGING CAMERA

- IR Resolution: 96×96 (9,216 pixels)
- SuperIR: 240×240 (57,600 pixels)
- NETD: < 50mK
- Image Frequency: 25Hz
- FOV: 50°×50°
- Visual Camera: 640×480 (0.3MP)
- Display: 3.5" LCD Touch Screen (320×240 resolution)
- Object Temp Range: -20°C ~ 350°C
- Accuracy: Max (±2°C)
- Storage: Built-in 4GB Flash (Approx. 30,000 images / 20h video)
- Connectivity: Wi-Fi (2.4GHz)
- Battery: Approx. 4 hours (USB Type-C)
- Durability: IP54, 2m Drop Protection
- Weight: Approx. 218g

EXCL. VAT 00  
R5299.00



### UTG962E FUNCTION/ARBITRARY WAVEFORM GENERATOR

- Channels: 2
- Max Frequency: 60MHz
- Sample Rate: 200MSa/s
- Vertical Resolution: 14 bits
- Waveforms: Sine, Square, Pulse, Ramp, Noise, DC, Arbitrary (24 sets)
- Sweep Modes: Linear, Logarithmic
- Modulation: AM, FM, PM, FSK
- Display: 4.3-inch TFT LCD (480×272)
- Interface: USB Device
- Power: DC 5V, 2A
- Design: Ultra-compact and portable palm-sized device

EXCL. VAT 00  
R12448.00



### POCKET2 HANDHELD THERMAL IMAGING CAMERA

- IR Resolution: 256×192 (49,152 pixels)
- NETD: < 40mK
- Image Frequency: 25Hz
- FOV: 50°×37.2°
- Visual Camera: 3264×2448 (8MP)
- Display: 3.5" LCD Touch Screen (640×480 resolution)
- Object Temp Range: -20°C ~ 400°C
- Accuracy: Max (±2°C)
- Storage: Built-in 16GB Flash (Up to 60,000 images / 54h video)
- Connectivity: Wi-Fi (2.4GHz)
- Battery: Approx. 4 hours (USB Type-C)
- Durability: IP54, 2m Drop Protection
- Weight: Approx. 218g

**HIKMICRO**  
TRUSTED PARTNER



# UNI-T®